



“X-in-1” L-band Combo Optical Amplifier

HYDRA-L Series



Description

The HYDRA-L series is ConsteleX L-band version of the "combo" solution, offering multiple low-noise amplifiers in a single benchtop package combining compactness and cost-effectiveness.

The product includes on/off key switch and current control for adjusting the emission status and pump current of the amplifiers. The front panel allows for monitoring the emission status, pump current and temperature. A serial interface with easy-to-use software is also available for remote operation of the HYDRA.

HYDRA-L is fully customizable: you are free to choose the number of ports and power configuration per port that will best fit your application.

Applications

- Photonics R&D
- CATV
- Gas Sensing
- Telecoms



Need both C- and L-band ?

The versatility of the HYDRA series allows the cost effective integration of both C- and L-band optical amplifiers in a single system.

HYDRA - L - Series			
Specification	Value	Units	Notes
Input wavelength range	1565-1605	nm	
Saturated Output Power	10 - 18	dBm	Pin = -6 dBm
Input Power	-10	dBm	
Small Signal Gain	> 28	dB	Pin = -20 dBm
Noise Figure (NF)	< 6	dB	
Environmental Conditions			
Operating Temperature	15 - 40	°C	
Storage Temperature	-20 to +50	°C	
Humidity	0 - 90 %		
Electrical & Mechanical Specifications			
Operating Voltage	85 - 264	VAC	@ 47-63 Hz
Interface	Serial		RS-232 & GUI
Power Consumption	40 - 80	W	depending on model
Dimensions	47 x 27 x 10	cm	
Ordering Information			
Order Code: HYDRA-L-W-X-Y-Z-FCAPC		W-Z: EDFA O/P powers	
Other connectors available upon request			
All information is accurate and subject to change without notice.			



LASER RADIATION
AVOID EXPOSURE TO BEAM
CLASS 3B LASER PRODUCT



thinking outside the box

ConsteleX Technology Enablers Ltd
Sorou 12, GR-15125
Marousi, Athens
Greece

Tel: +30 211 800 5152
Fax: +30 211 800 5565
email: info@constelex.eu

www.constelex.eu